

NEPTUNE UL TL-30 SAFES

- ✦ UL TL-30 certified
- ✦ 2 hour factory fire protection
- ✦ Large 1.5" diameter chrome plated steel bolts and force resistive handle
- ✦ 2.5" thick construction body and 4" thick construction door
- ✦ UL certified Group 2M manipulation resistant combination lock with spy proof dial (other lock options available)
- ✦ 1/2" Ballistic Steel plate inside the door protecting the locks from frontal attack
- ✦ 1/4" thick Ballistic Steel plate inside the body protecting the bolts from side attack
- ✦ Additional 1/4" thick full size Ballistic Steel plate barrier increasing protection from frontal attack
- ✦ Full composite construction comprised of the highest quality barrier material enclosed within heavy steel plates (12Ga steel body, 1/4" thick steel door & frame, additional layer Ballistic steel barrier)
- ✦ Sophisticated Glass Protected Relocking System is activated and locked when attacked
- ✦ High quality 1.5" diameter heavy duty adjustable hinges
- ✦ Custom sizes and interiors available



MODEL	INTERIOR			EXTERIOR			SHELVES	VOLUME (ft. ³)	WEIGHT (lbs.)	
	Name	Height (in.)	Width (in.)	Depth (in.)	Height (in.)	Width (in.)				Depth (in.)
TL - 30 1212		12	12	10	17	17	19 1/2	1	0.83	450
TL - 30 2014		20	14	13 3/4	25	19	23 1/2	1	2.25	755
TL - 30 2517		25	17	13 3/4	30	22	23 1/2	1	3.40	930
TL - 30 3219		32	19	15 3/4	37	24	25 1/2	2	5.54	1230
TL - 30 4520		45	20	20 3/4	50	25	30 1/2	3	10.81	1796
TL - 30 5520		55	20	20 3/4	60	25	30 1/2	4	13.21	2280
TL - 30 6523		65	23	20 3/4	70	28	30 1/2	5	17.95	2700
TL - 30 6532		65	32	20 3/4	70	37	30 1/2	5	24.98	3300
TL - 30 7437		74	37	20 3/4	79	44	30 1/2	5	32.88	4250

* Dimensions do NOT include hinges, locks, handle